

# CB919

## Benefits and Features

- Aggressive lug design with large block at tread center designed for mining, rock and quarry operations
- Wide tread and special tread compounds resist chipping, chunking, and tearing
- Stone ejector platform prevents trapped stones from punching deeper and piecing belt



Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single		Dual	
							(kg)	(kPa)	(kg)	(kPa)
11.00R20	J/18	152/149F	25.5	8.0	1096	293	3550	930	3250	930
12.00R20	J/18	154/151F	25.5	8.5	1136	315	3750	830	3450	830
12.00R20	M/22	158/155C	25.5	8.5	1136	315	4250	970	3875	970
11R22.5	G/14	144/142G	23.0	8.25	1065	279	2800	720	2650	720
11R22.5	H/16	148/145J	23.0	8.25	1065	279	3150	850	2900	850
12R22.5	H/16	150/147F	23.5	9.00	1096	300	3350	830	3075	830
12R22.5	J/18	152/149F	23.5	9.00	1096	300	3550	930	3250	930
13R22.5	J/18	156/151F	24.0	9.75	1136	320	4000	875	3450	875

Source : Trazano

Disclaimer: All product information and applications contained in this page may be subject to change without notice.