

CM958

Benefits and Features

- Multiple gripping edges slice through water and road films for a solid grip
- Four wide continuous rib design help resist tread squirm and heel-and-tow wear for exceptionally long tread life
- Three circumferential grooves help deliver all-season traction on wet or dry road
- Closed shoulder design helps promote even wear throughout the tyre life



Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single		Dual	
							(kg)	(kPa)	(kg)	(kPa)
7.50R15	H/16	135/133J	13.0	6.0	780	212	2180	850	2060	850
8.25R15	J/18	143/141J	14.0	6.50	836	234	2725	850	2575	850
7.00R16	G/14	118/114L	14.0	5.50F	785	200	1320	770	1180	770
7.50R16	G/14	122/118L	15.5	6.00G	815	215	1500	770	1320	770
8.25R20	H/16	139/137K	14.0	6.5	974	236	2430	930	2300	930
8.25R16	H/16	128/124L	16.0	6.50H	865	235	1800	770	1600	770
9.00R20	H/16	144/142K	16.0	7.0	1019	259	2800	900	2650	900
10.00R20	H/16	146/143K	15.0	7.5	1054	278	3000	830	2725	830
10.00R20	J/18	149/146J	15.0	7.5	1054	278	3250	930	3000	930
11.00R20	H/16	150/147K	16.0	8.0	1085	293	3350	830	3075	830
11.00R20	J/18	152/149K	16.0	8.0	1085	293	3550	930	3250	930
12.00R20	J/18	154/151K	17.0	8.5	1125	315	3750	830	3450	830
215/75R17.5	G/14	126/124M	13.0	6.00	767	211	1700	760	1600	760

215/75R17.5	H/16	135/133J	13.0	6.00	767	211	2180	850	2060	850
8R22.5	F/12	128/127M	13.5	6.00	935	203	1800	760	1750	760
8R22.5	G/14	130/128M	13.5	6.00	935	203	1900	830	1800	830
9R22.5	F/12	133/131M	14.0	6.75	974	229	2060	720	1950	720
9R22.5	G/14	136/134M	14.0	6.75	974	229	2240	830	2120	830
10R22.5	G/14	141/139M	15.0	7.50	1019	254	2575	790	2430	790
10R22.5	H/16	144/142M	15.0	7.50	1019	254	2800	900	2650	900
11R22.5	G/14	144/142M	17.5	8.25	1054	279	2800	720	2650	720
11R22.5	H/16	148/145L	17.5	8.25	1054	279	3150	850	2900	850
12R22.5	H/16	150/147L	18.0	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	18.0	9.00	1085	300	3550	930	3250	930
13R22.5	J/18	156/150K	20.0	9.75	1124	320	4000	875	3350	875
13R22.5	J/18	156/151K	20.0	9.75	1124	320	4000	875	3450	875
255/70R22.5	H/16	140/137L	15.0	7.50	930	255	2500	830	2300	830
295/80R22.5	H/16	150/147M	18.0	9.00	1044	298	3350	830	3075	830
315/80R22.5	L/20	157/154K	18.0	9.00	1082	312	4125	900	3750	900
295/80R22.5	J/18	152/149M	18.0	9.00	1044	298	3550	900	3250	900
315/80R22.5	H/16	151/148M	18.0	9.00	1082	312	3450	760	3150	760
315/80R22.5	J/18	154/151M(156/150L)	18.0	9.00	1082	312	3750	830	3450	830

Source : Trazano

Disclaimer: All product information and applications contained in this page may be subject to change without notice.