

CR960A

Benefits and Features

- Improved close shoulder helps to improve even wear resulting in long tread life
- Straight simple rib pattern improves even wearing and efficient water evacuation for excellent wet traction and handling



Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single		Dual	
							(kg)	(kPa)	(kg)	(kPa)
7.50R16	G/14	122/118L	12.0	6.00G	805	215	1500	770	1320	770
8.25R16	G/14	128/126 L	13.0	6.50H	855	235	1800	670	1700	670
8.25R16	H/16	128/124L	13.0	6.50H	855	235	1800	770	1600	770
ST235/85R16	G/14	129/125L	10.5	1/2J	806	235	1850	760	1650	760
245/70R17.5	J/18	143/141J	13.0	7.50	789	248	2725	875	2575	875
245/70R17.5	H/16	136/134M	13.0	7.50	789	248	2240	850	2120	850
205/75R17.5	F/12	122/120M	12.0	6.00	753	205	1500	675	1400	675
205/75R17.5	G/14	124/122M	12.0	6.00	753	205	1600	750	1500	750
215/75R17.5	G/14	126/124M	12.5	6.00	767	211	1700	760	1600	760
215/75R17.5	H/16	135/133J	12.5	6.00	767	211	2180	850	2060	850
225/75R17.5	F/12	126/125M	12.5	6.75	783	226	1700	675	1650	675
225/75R17.5	G/14	129/127M	12.5	6.75	783	226	1850	725	1750	725
235/75R17.5	F/12	130/128M	13.3	6.75	797	233	1900	725	1800	725

235/75R17.5	G/14	132/130M	13.3	6.75	797	233	2000	775	1900	775
235/75R17.5	H/16	143/141J	13.3	6.75	797	233	2725	875	2575	875
8R19.5	F/12	124/122L	13.0	6.00	859	203	1600	760	1500	760
225/70R19.5	F/12	125/123M	13.0	6.75	811	226	1650	660	1550	660
245/70R19.5	G/14	133/131M	13.0	7.50	839	248	2060	760	1950	760
245/70R19.5	H/16	136/134M	13.0	7.50	839	248	2240	830	2120	830
285/70R19.5	G/14	140/137M	14.5	8.25	895	283	2500	725	2300	725
285/70R19.5	H/16	146/144K	14.5	8.25	895	283	3000	850	2800	850
11R22.5	G/14	144/142L	14.2	8.25	1054	279	2800	720	2650	720
11R22.5	H/16	148/145M	14.2	8.25	1054	279	3150	850	2900	850
12R22.5	H/16	150/147L	15.5	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	15.5	9.00	1085	300	3550	930	3250	930
315/70R22.5	J/18	152/148M	15.0	9.00	1014	312	3550	850	3150	850
315/70R22.5	L/20	154/150L	15.0	9.00	1014	312	3750	900	3350	900
295/75R22.5	G/14	144/141L	14.2	9.00	1014	298	2800	760	2575	760
295/75R22.5	H/16	146/143L	14.2	9.00	1014	298	3000	830	2725	830
315/80R22.5	H/16	151/148M	15.0	9.00	1076	312	3450	760	3150	760
315/80R22.5	J/18	154/151M(156/150L)	15.0	9.00	1076	312	3750	830	3450	830
315/80R22.5	L/20	157/154K	15.0	9.00	1076	312	4125	900	3750	900
11R24.5	G/14	146/143L	14.2	8.25	1104	279	3000	720	2725	720
11R24.5	H/16	149/146L	14.2	8.25	1104	279	3250	830	3000	830

Source : Trazano

Disclaimer: All product information and applications contained in this page may be subject to change without notice.