

CR976A

Benefits and Features

- Five ribs with four wide, straight grooves for precise handling and outstanding traction
- Stone ejector platforms prevent stones from lodging in grooves and drilling into belts
- Shallower tread depth helps to resist treadsquirm and irregular wear forces for exceptionally long mileage



Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single		Dual	
							(kg)	(kPa)	(kg)	(kPa)
385/65R22.5	J/18	158L(160K)	15.5	11.75	1072	389	4250	850	-	-
385/65R22.5	L/20	160K(158L)	15.5	11.75	1072	389	4500	900	-	-
425/65R22.5	L/20	165K	15.0	13.00	1124	430	5150	830	-	-
445/65R22.5	L/20	169K	15.0	13.00	1150	444	5800	900	-	-
9.00R20	G/14	141/139K	14.5	7.0	1019	259	2575	790	2430	790
9.00R20	H/16	144/142L	14.5	7.0	1019	259	2800	900	2650	900
9.00R20	H/16	144/142K	14.5	7.0	1019	259	2800	900	2650	900
10.00R20	H/16	146/143K	15.0	7.5	1054	278	3000	830	2725	830
10.00R20	H/16	146/143L	15.0	7.5	1054	278	3000	830	2725	830
10.00R20	J/18	149/146J	15.0	7.5	1054	278	3250	930	3000	930
11.00R20	H/16	150/147K	15.5	8.0	1085	293	3350	830	3075	830
11.00R20	J/18	152/149K	15.5	8.0	1085	293	3550	930	3250	930
12.00R20	J/18	154/151K	17.0	8.5	1125	315	3750	830	3450	830

215/75R17.5	G/14	126/124M	12.5	6.00	767	211	1700	760	1600	760
215/75R17.5	H/16	135/133J	12.5	6.00	767	211	2180	850	2060	850
225/70R19.5	F/12	125/123M	13.0	6.75	811	226	1650	660	1550	660
225/70R19.5	G/14	128/126M	13.0	6.75	811	226	1800	760	1700	760
245/70R19.5	G/14	133/131M	13.0	7.50	839	248	2060	760	1950	760
245/70R19.5	H/16	136/134M	13.0	7.50	839	248	2240	830	2120	830
265/70R19.5	G/14	137/134M	14.0	7.50	867	262	2300	760	2120	760
265/70R19.5	H/16	140/138M	14.0	7.50	867	262	2500	775	2360	775
265/70R19.5	J/18	143/141J	14.0	7.50	867	262	2725	850	2575	850
11R22.5	G/14	144/142M	15.5	8.25	1054	279	2800	720	2650	720
11R22.5	H/16	148/145M	15.5	8.25	1054	279	3150	850	2900	850
12R22.5	H/16	150/147L	15.5	9.00	1085	300	3350	830	3075	830
275/80R22.5	H/16	149/146M	14.0	8.25	1012	276	3250	850	3000	850
12R22.5	J/18	152/149L	15.5	9.00	1085	300	3550	930	3250	930
255/70R22.5	H/16	140/137M	14.5	7.50	930	255	2500	830	2300	830
275/70R22.5	H/16	148/145M	14.0	8.25	958	276	3150	900	2900	900
275/70R22.5	J/18	152/148J	14.0	8.25	958	276	3550	930	3150	930
295/80R22.5	H/16	150/147M	15.0	9.00	1044	298	3350	830	3075	830
315/80R22.5	L/20	157/154K	16.0	9.00	1076	312	4125	900	3750	900
295/80R22.5	J/18	152/149M	15.0	9.00	1044	298	3550	900	3250	900
315/80R22.5	H/16	151/148M	16.0	9.00	1076	312	3450	760	3150	760
315/80R22.5	J/18	154/151M(156/150L)	16.0	9.00	1076	312	3750	830	3450	830

Source : Trazano

Disclaimer: All product information and applications contained in this page may be subject to change without notice.