

# MD738

## Benefits and Features

- Excellent traction for ON/OFF drive axle application
- Aggressive and optimum self-cleaning tread with lateral grooves provides remarkable performance in all weather conditions both one and off the roads



Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single		Dual	
							(kg)	(kPa)	(kg)	(kPa)
9.5R17.5	G/14	129/127L	16.5	6.75	842	240	1850	750	1750	750
9.5R17.5	H/16	143/141J	16.5	6.75	842	240	2725	875	2575	875
11R22.5	G/14	144/142L	20.6	8.25	1065	279	2800	720	2650	720
11R22.5	H/16	148/145L	20.6	8.25	1065	279	3150	850	2900	850
12R22.5	H/16	150/147L	20.6	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	20.6	9.00	1085	300	3550	930	3250	930
275/70R22.5	H/16	148/145J	18.0	8.25	964	276	3150	900	2900	900
275/70R22.5	J/18	152/148J	18.0	8.25	964	276	3550	930	3150	930
295/80R22.5	H/16	150/147L	20.6	9.00	1050	298	3350	830	3075	830
295/80R22.5	J/18	152/149L	20.6	9.00	1050	298	3550	900	3250	900
11R24.5	G/14	146/143L	22.6	8.25	1116	279	3000	720	2725	720
11R24.5	H/16	149/146L	22.6	8.25	1116	279	3250	830	3000	830

Source : Trazano

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

© SUNLUN Group, All Rights Reserved

For more information, please visit [www.sunlun.com.my](http://www.sunlun.com.my)